

According to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS Reference Number: SDS-23625-5
Issue date: 6/24/2025 Version: 1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product form : Mixture
Trade name : MAGELLAN AFX520 ECOMAR Red
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses
Main use category : Industrial use, Professional use
Use of the substance/mixture : Paint. For professional users/industrial user only.
Uses advised against
Restrictions on use : All uses not specified in this section or in section 7.3

1.3. Details of the supplier of the safety data sheet

Supplier

Vilckens Boyaları San. Tic. Ltd.
Postane Mahallesi Esentepe Caddesi
Manastır Yolu No:21
34940 Tuzla / İstanbul
Türkiye
T 0212 356 93 56 - F 0212 356 95 00

1.4. Emergency telephone number

No additional information available

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]
Flammable liquids, Category 3 H226
Acute toxicity (dermal), Category 4 H312
Acute toxicity (inhal.), Category 4 H332
Skin corrosion/irritation, Category 2 H315
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Acute Hazard, Category 1 H400
Hazardous to the aquatic environment – Chronic Hazard, Category 1 H410

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects. Flammable liquid and vapour.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS09

Signal word (CLP) :

Warning

Contains :

Xylene; Rosin; Copper oxide; Zineb (ISO)

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.
H312+H332 - Harmful in contact with skin or if inhaled.

Precautionary statements (CLP)

- H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H410 - Very toxic to aquatic life with long lasting effects.
- : P210 - Keep away from heat, hot surfaces, open flames, sparks. – No smoking.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing/eye protection/face protection.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P370+P378 - In case of fire: Use ABC-powder for extinction.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS
3.2. Mixtures

Comments : Miscellaneous products

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Xylene (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	10 – 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315
Rosin	CAS-No.: 8050-09-7 EC-No.: 232-475-7 EC Index-No.: 650-015-00-7	10 – 25	Skin Sens. 1, H317
Copper oxide	CAS-No.: 1317-38-0 EC-No.: 215-269-1 EC Index-No.: 029-016-00-6	10 – 25	Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)
Copper thiocyanate	CAS-No.: 1111-67-7 EC-No.: 214-183-1 EC Index-No.: 029-015-00-0	10 – 25	Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
zinc oxide	CAS-No.: 1314-13-2 EC-No.: 215-222-5 EC Index-No.: 030-013-00-7	2.5 – 10	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
N-butyl acetate	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1	2.5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066



Zineb (ISO)	CAS-No.: 12122-67-7 EC-No.: 235-180-1 EC Index-No.: 006-078-00-2	2.5 – 10	Skin Sens. 1, H317 STOT SE 3, H335
Alkanes, chloro	CAS-No.: 61788-76-9 EC-No.: 263-004-3	1 – 2.5	Aquatic Chronic 4, H413

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H- and EUH-statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

First-aid measures general	:	In all cases of doubt, or when symptoms persist, seek medical attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	:	Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	:	Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	:	Rinse eyes with water as a precaution.
First-aid measures after ingestion	:	Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	:	Harmful if inhaled.
Symptoms/effects after skin contact	:	Harmful in contact with skin. Irritation. May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media	:	Water spray. Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO ₂).
Unsuitable extinguishing media	:	Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard	:	Contact with combustible material may cause fire.
Explosion hazard	:	Risk of explosion if heated under confinement.
Hazardous decomposition products in case of fire	:	On heating or during combustion : Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire	:	Keep away from combustible materials. Keep container closed when not in use. Approach from upwind.
Firefighting instructions	:	Exercise caution when fighting any chemical fire. Keep upwind. Do not enter fire area without proper protective equipment, including respiratory protection. Eliminate all ignition sources if safe to do so. Contain the extinguishing fluids by bunding.
Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	:	Do not allow run-off from fire fighting to enter drains or water courses. Notify authorities if product enters sewers or public waters. High temperature decomposition products are harmful by inhalation. Inhalation of vapour can cause breathing difficulties.



SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Keep public away from danger area.
- For non-emergency personnel
- Protective equipment : For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Ventilate spillage area. Do not touch or walk on the spilled product. Notify fire brigade and environmental authorities. Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray.
- For emergency responders
- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate unnecessary personnel. Equip cleanup crew with proper protection. Stop leak if safe to do so. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Do not touch or walk on the spilled product. Collect spillage.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool well ventilated place.
- Incompatible products : Strong acids. Strong bases. Strong oxidizing agents.
- Incompatible materials : Extremely high or low temperatures.
- Maximum storage period : 6 months
- Storage temperature : 5 – 30 °C
- Heat and ignition sources : Keep away from heat and direct sunlight. Keep away from sources of ignition.
- Information on mixed storage : Keep away from food, drink and animal feeding stuffs.
- Storage area : Store, if possible, in a cool, well ventilated place away from incompatible materials.
- Germany
- Storage class (LGK, TRGS 510) : LGK 3 - Flammable liquids
- Joint storage table :

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

- Joint storage not permitted for : LGK 1, LGK 2A, LGK 4.1A, LGK 4.1B, LGK 4.2, LGK 4.3, LGK 5.1A, LGK 5.1C, LGK 5.2, LGK 6.1B, LGK 6.2, LGK 7
- Joint storage with restrictions permitted for : LGK 5.1B, LGK 6.1D, LGK 11, LGK 10-13

Joint storage permitted for : LGK 2B, LGK 3, LGK 6.1A, LGK 6.1C, LGK 8A, LGK 8B, LGK 10, LGK 12, LGK 13

7.3. Specific end use(s)

See Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

National occupational exposure and biological limit values

Xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m ³ (pure) 50 ppm (pure)
IOEL STEL	442 mg/m ³ (pure) 100 ppm (pure)
Remark	Possibility of significant uptake through the skin (pure)
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Xylol (alle Isomere)
AGW (OEL TWA)	220 mg/m ³ (all isomers) 50 ppm (all isomers)
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); H - hautresorptiv
Chemical category	Skin notation all isomers
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Xylol (alle Isomere)
Biological limit value	2000 mg/l Parameter: Methylhippuric(tolur-)acid (all isomers) - Medium: urine - Sampling time: end of exposure or shift (all isomers)
Regulatory reference	TRGS 903

Copper oxide (1317-38-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Copper(II) oxide
IOEL TWA	0.01 mg/m ³ (respirable fraction)
Remark	(Year of adoption 2014)
Regulatory reference	SCOEL Recommendations



N-butyl acetate (123-86-4)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	n-Butyl acetate
IOEL TWA	241 mg/m ³ 50 ppm
IOEL STEL	723 mg/m ³ 150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831

Germany - Occupational Exposure Limits (TRGS 900)

Local name	n-Butylacetat
AGW (OEL TWA)	300 mg/m ³ 62 ppm
Peak exposure limitation factor	2(l)
Remark	AGS - Ausschuss für Gefahrstoffe; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich)
Regulatory reference	TRGS900

DNEL and PNEC

Xylene (1330-20-7)

DNEL/DMEL (Workers)

Acute - systemic effects, inhalation	442 mg/m ³
Acute - local effects, inhalation	442 mg/m ³
Long-term - systemic effects, dermal	212 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	221 mg/m ³
Long-term - local effects, inhalation	221 mg/m ³

DNEL/DMEL (General population)

Acute - systemic effects, inhalation	260 mg/m ³
Acute - local effects, inhalation	260 mg/m ³
Long-term - systemic effects, oral	12.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	65.3 mg/m ³
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - local effects, inhalation	65.3 mg/m ³

PNEC (Water)

PNEC aqua (freshwater)	0.327 mg/l
PNEC aqua (marine water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l

PNEC (Sediment)

PNEC sediment (freshwater)	12.46 mg/kg dwt
----------------------------	-----------------



PNEC sediment (marine water)	12.46 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.31 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	6.58 mg/l

Rosin (8050-09-7)

DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	2.131 mg/kg bodyweight/day
Long-term - local effects, inhalation	10 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	1.0655 mg/kg bodyweight/day
Long-term - systemic effects, dermal	1.0655 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.0016 mg/l
PNEC aqua (marine water)	0.00016 mg/l
PNEC aqua (intermittent, freshwater)	0.016 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.007 mg/kg dwt
PNEC sediment (marine water)	0.0007 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.00045 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	1000 mg/l

Copper oxide (1317-38-0)

DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	137 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1 mg/m ³
Long-term - local effects, inhalation	1 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, oral	0.082 mg/kg bodyweight/day
Long-term - systemic effects, oral	0.041 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	7.8 µg/l
PNEC aqua (marine water)	5.2 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	87 mg/kg dwt



PNEC sediment (marine water)	676 mg/kg dwt
PNEC (Soil)	
PNEC soil	65 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	230 µg/l

zinc oxide (1314-13-2)

DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	83 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	5 mg/m ³
Long-term - local effects, inhalation	0.5 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0.83 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.5 mg/m ³
Long-term - systemic effects, dermal	83 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	20.6 µg/l
PNEC aqua (marine water)	6.1 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	117.8 mg/kg dwt
PNEC sediment (marine water)	56.5 mg/kg dwt
PNEC (Soil)	
PNEC soil	35.6 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 µg/l

N-butyl acetate (123-86-4)

PNEC (Water)	
PNEC aqua (freshwater)	0.18 mg/l
PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.0903 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	35.6 mg/l



8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Gloves. Safety glasses. Wear protective clothing. Wear foot protection. Gas mask.

Personal protective equipment symbol(s):



Eye protection:

Safety glasses. Use splash goggles when eye contact due to splashing is possible

Skin and body protection:

According to the conditions of use, protective gloves, apron, boots, head and face protection must be worn

Hand protection:

Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. The breakthrough time of the selected gloves must be greater than the intended use period. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. [In case of inadequate ventilation] wear respiratory protection.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Red
Molecular mass	: 107.8 g/mol
Odour	: According to product specification
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 135 °C
Flammability	: Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 25 °C
Auto-ignition temperature	: 421 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 0.98 mm ² /s
Viscosity, dynamic	: 1.56 cP
Solubility	: Not available
Partition coefficient n-octanol/water (Log K _{ow})	: Not available
Vapour pressure	: 823 Pa



Vapour pressure at 50°C	: 4435.99 Pa
Density	: 1470 – 1530 kg/m ³
Relative density	: 1.47 – 1.53
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics	
VOC content	: 25 %
Average carbon number	: 7,68

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Increase in temperature causes risk of combustion. Avoid direct impact with sunlight.

10.5. Incompatible materials

Avoid strong acids, Avoid direct impact with oxidising materials, avoid alkalis or strong bases.

10.6. Hazardous decomposition products

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Harmful in contact with skin.
Acute toxicity (inhalation)	: Harmful if inhaled.

MAGELLAN AFX520 ECOMAR Red

ATE CLP (dermal)	1100 mg/kg bodyweight
ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h

Xylene (1330-20-7)

LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
--------------------	---

Rosin (8050-09-7)

LD50 oral rat	7800 mg/kg Source: IUCLID
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))



LD50 dermal rabbit	2500 mg/kg
LD50 dermal	2500 mg/kg
LC50 Inhalation - Rat	2.3 mg/l
LC50 Inhalation - Rat (Dust/Mist)	2.3 mg/l/4h

Copper oxide (1317-38-0)

LD50 oral rat	> 2500 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

zinc oxide (1314-13-2)

LD50 oral rat	≥ 5000 (2000 – 5000) mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	1.79 – 5.7 mg/l/4h

N-butyl acetate (123-86-4)

LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	10736 mg/kg
LD50 dermal rabbit	> 14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal	17600 mg/kg
LC50 Inhalation - Rat	0.74 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
LC50 Inhalation - Rat (Vapours)	1802 mg/l/4h Source: ECHA

Skin corrosion/irritation : Causes skin irritation.

N-butyl acetate (123-86-4)

pH	6.2 Temp.: 20 °C Concentration: 5,3 g/L
----	---

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)

N-butyl acetate (123-86-4)

pH	6.2 Temp.: 20 °C Concentration: 5,3 g/L
----	---

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)



STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

zinc oxide (1314-13-2)	
NOAEL (oral, rat)	31.52 mg/kg bodyweight

N-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

Zineb (ISO) (12122-67-7)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

zinc oxide (1314-13-2)	
LOAEL (dermal, rat/rabbit, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (oral, rat, 90 days)	31.52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	500 µg/m ³

N-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

MAGELLAN AFX520 ECOMAR Red	
Viscosity, kinematic	0.98 mm ² /s

Xylene (1330-20-7)	
Viscosity, kinematic	0.74 mm ² /s

N-butyl acetate (123-86-4)	
Viscosity, kinematic	0.83 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'

11.2. Information on other hazards

No additional information available

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic) : Very toxic to aquatic life with long lasting effects.



Xylene (1330-20-7)

LC50 - Fish [1]	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	2.661 – 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 - Crustacea [2]	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

Rosin (8050-09-7)

LC50 - Fish [1]	5.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Fish [2]	5.4 mg/l Test organisms (species):
EC50 - Crustacea [1]	4.5 mg/l

zinc oxide (1314-13-2)

LC50 - Fish [1]	112 – 8062 µg/l
EC50 - Crustacea [1]	155 – 100000 µg/l
NOEC chronic fish	530 µg/l
NOEC chronic crustacea	300 µg/l
NOEC chronic algae	1071 mg/l

N-butyl acetate (123-86-4)

LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
EC50 72h - Algae [1]	397 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
ErC50 algae	397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic algae	296 mg/l

12.2. Persistence and degradability
MAGELLAN AFX520 ECOMAR Red

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Xylene (1330-20-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------



Rosin (8050-09-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Copper oxide (1317-38-0)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Copper thiocyanate (1111-67-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

zinc oxide (1314-13-2)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

N-butyl acetate (123-86-4)

Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O ₂ /g substance

Zineb (ISO) (12122-67-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Alkanes, chloro (61788-76-9)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential
Xylene (1330-20-7)

BCF - Fish [1]	0.6 – 15
Partition coefficient n-octanol/water (Log Pow)	2.77 – 3.15

N-butyl acetate (123-86-4)

Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil
N-butyl acetate (123-86-4)

Surface tension	61.3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Results of PBT and vPvB assessment
Component

Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Xylene (1330-20-7), N-butyl acetate (123-86-4)
--	--



Component

Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII Xylene (1330-20-7), N-butyl acetate (123-86-4)

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations: Completely empty the packaging prior to decontamination. Recycle the material as far as possible. Comply with local regulations for disposal.
Ecological waste information : Avoid release to the environment.
European List of Waste (LoW, EC 2000/532) : 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: TRANSPORT INFORMATION

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT	PAINT	Paint	PAINT	PAINT
Transport document description				
UN 1263 PAINT, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes



No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR)	:	F1
Special provisions (ADR)	:	163, 367, 650
Limited quantities (ADR)	:	5I
Excepted quantities (ADR)	:	E1
Packing instructions (ADR)	:	P001, IBC03, LP01, R001
Special packing provisions (ADR)	:	PP1
Mixed packing provisions (ADR)	:	MP19
Portable tank and bulk container instructions (ADR)	:	T2
Portable tank and bulk container special provisions (ADR)	:	TP1, TP29
Tank code (ADR)	:	LGBF
Vehicle for tank carriage	:	FL
Transport category (ADR)	:	3
Special provisions for carriage - Packages (ADR)	:	V12
Special provisions for carriage - Operation (ADR)	:	S2
Hazard identification number (Kemler No.)	:	30
Orange plates	:	30 1263

Tunnel restriction code (ADR) : D/E

Transport by sea

Special provisions (IMDG)	:	163, 223, 367, 955
Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E1
Packing instructions (IMDG)	:	P001, LP01
Special packing provisions (IMDG)	:	PP1
IBC packing instructions (IMDG)	:	IBC03
Tank instructions (IMDG)	:	T2
Tank special provisions (IMDG)	:	TP1, TP29
Stowage category (IMDG)	:	A
Properties and observations (IMDG)	:	Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y344
PCA limited quantity max net quantity (IATA)	:	10L
PCA packing instructions (IATA)	:	355
PCA max net quantity (IATA)	:	60L
CAO packing instructions (IATA)	:	366
CAO max net quantity (IATA)	:	220L
Special provisions (IATA)	:	A3, A72, A192
ERG code (IATA)	:	3L

Inland waterway transport

Classification code (ADN)	:	F1
Special provisions (ADN)	:	163, 367, 650
Limited quantities (ADN)	:	5 L



Excepted quantities (ADN) : E1
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 0

Rail transport
Classification code (RID) : F1
Special provisions (RID) : 163, 367, 650
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T2
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals):
Zineb (12122-67-7)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 25 %

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

Germany



Employment restrictions	:	Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	:	WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
Major Accidents Ordinance (12. BImSchV)	:	Is not subject to the Major Accidents Ordinance (12. BImSchV)
VOC content	:	25 %

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant



ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
IOELV	Indicative Occupational Exposure Limit Value
Pow (log)	n-octanol/water partition coefficient
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
WGK	Water Hazard Class

Data sources : Classification according to Regulation (EC) No. 1272/2008 [CLP]. ECHA (European Chemicals Agency). Supplier's safety documents.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.



Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
Acute Tox. 4 (Dermal)	H312	Calculation method
Acute Tox. 4 (Inhalation)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method

The classification complies with : ATP 12
Safety Data Sheet (SDS), EU

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable

